



RFID incoming and outgoing goods registration system

Gate Solution Master package - sensor



| Application            |     |                                                                                                                        |
|------------------------|-----|------------------------------------------------------------------------------------------------------------------------|
| Design                 |     | Master-Package mit Laser-Reflexlichtschranke                                                                           |
| Radio approval for     |     | EU/RED                                                                                                                 |
| Note on radio approval |     | radio approval for the RFID evaluation unit DTE830                                                                     |
|                        |     | The list of countries applying the European Radio Equipment Directive 2014/53/EU (RED) can be found under “Downloads”. |
| Electrical data        |     |                                                                                                                        |
| Operating voltage      | [V] | 20...30 DC                                                                                                             |
| Mechanical data        |     |                                                                                                                        |
| Weight                 | [g] | 23000                                                                                                                  |



## RFID incoming and outgoing goods registration system

Gate Solution Master package - sensor

| Accessories            |                                                                    |
|------------------------|--------------------------------------------------------------------|
| Items supplied         | edgeController für UHF-Gate-Solution: 1, ZZ1124                    |
|                        | Connection cable: 1, E70450                                        |
|                        | RFID evaluation unit UHF: 1, DTE830                                |
|                        | RFID UHF antenna: 4, ANT860                                        |
|                        | Connection cable: 4, E80332                                        |
|                        | Ethernet switch: 1, AL3050                                         |
|                        | IO-Link master: 1, AL1122                                          |
|                        | Retro-reflective laser sensor: 2, OGP700                           |
|                        | Reflector for retro-reflective laser sensors: 2, E20722            |
|                        | 5-segment light tower: 1, DV2510                                   |
|                        | Connection cable: 3, EVC108                                        |
|                        | Power supply: 1, DN4012                                            |
|                        | Connecting cable with socket: 4, EVC003                            |
|                        | Connecting cable with socket: 1, E12166                            |
|                        | Connecting cable with socket: 1, E12492                            |
|                        | Connection cable: 3, E21137                                        |
|                        | Adapter cable: 1, E80412                                           |
| Accessories (optional) | extension package with 3D sensor, ZZ0815                           |
|                        | extension package with retro-reflective laser sensor, ZZ0817       |
| Remarks                |                                                                    |
| Remarks                | Article is preprogrammed specifically for the Application Package. |
|                        | loading direction detection via retro-reflective sensors           |
| Pack quantity          | 1 pcs.                                                             |